

# Euro 6e-bis

WHEELBASE 3125 mm

## Steel rear tipper



Code	Boards	External Dimensions
M 155 025 019	Flat aluminum	1890x1845 mm

Anodized aluminium sideboards from 300 mm top opening only

Anodized aluminium tailgate height 300 mm with double opening and automatic release



Structure of the loading deck in single thick in steel sheet. 3 mm

Steel sub-frame

Aluminum front board from 300 mm with ladder rack steel painted

Anodized aluminium side boards from 300 mm with integrated handles

Anodized aluminium rear board from 300 mm

Front and rear pillars screwed

Recessed foldway rope stretching ring (2+2)

Thermoplastic mudguards

Tool box

Electro-hydraulic power pack with control panel into cab, isolation switch, safety fuse and buzzer

Chromed multistage under floor ram, wear resistant, weather resistant and rust resistant with safety valve

Underrun protection crossbar and approved towing preparation

Cataphoresis treatment and powder coating

Lights according to regulations

**\* AWAITING EQUIPMENT TYPE APPROVAL**

Overall dimensions with equipment L= 6280 mm

NOTE: The information and images - including the colors of the products - concerning equipment, external appearance, measurements, etc. are to be considered purely indicative and in no way binding.

TITAN reserves the right to change features, specifications, data, prices without notice. The prices indicated on the Site are in no way binding for contractual purposes and may vary according to the duration of the price list. Prices are always VAT free.

For updated and punctual information on products and prices, TITAN invites users to contact its sales network.

€ 5.750,00

# Euro 6e-bis

WHEELBASE 3125 mm

## Steel rear tipper



Code	Boards	External Dimensions
M 155 025 022	Flat aluminum	2400x1845 mm

Anodized aluminium sideboards from 300 mm top opening only

Anodized aluminium tailgate height 300 mm with double opening and automatic release



Structure of the loading deck in single thick in steel sheet. 3 mm

Steel sub-frame

Aluminum front board from 300 mm with ladder rack steel painted

Anodized aluminium side boards from 300 mm with integrated handles

Anodized aluminium rear board from 300 mm

Front and rear pillars screwed

Recessed foldway rope stretching ring (2+2)

Thermoplastic mudguards

Tool box

Electro-hydraulic power pack with control panel into cab, isolation switch, safety fuse and buzzer

Chromed multistage under floor ram, wear resistant, weather resistant and rust resistant with safety valve

Underrun protection crossbar and approved towing preparation

Cataphoresis treatment and powder coating

Lights according to regulations

**\* AWAITING EQUIPMENT TYPE APPROVAL**

Overall dimensions with equipment L= 5320 mm

NOTE: The information and images - including the colors of the products - concerning equipment, external appearance, measurements, etc. are to be considered purely indicative and in no way binding.

TITAN reserves the right to change features, specifications, data, prices without notice. The prices indicated on the Site are in no way binding for contractual purposes and may vary according to the duration of the price list. Prices are always VAT free.

For updated and punctual information on products and prices, TITAN invites users to contact its sales network.

€ 6.062,50

# Euro 6e-bis

WHEELBASE 3125 mm

## Alloy rear tipper



Code	Boards	External Dimensions
M 155 026 708*	Flat aluminum	1890x1830 mm

Anodized aluminium sideboards from 300 mm top opening only

Anodized aluminium tailgate height 300 mm with double opening and automatic release

Structure of the loading deck in single thick in aluminum sheet. 4 mm

Galvanized steel sub-frame

Aluminum front board from 300 mm with ladder rack and perforated protection panel in aluminium painted

Anodized aluminium side boards from 300 mm with integrated handles

Anodized aluminium rear board from 300 mm

Rear pillars removable with integrated handles

Recessed foldway rope stretching ring (2+2)

Thermoplastic mudguards

Tool box

Electro-hydraulic power pack with control panel into cab, isolation switch, safety fuse and buzzer

Chromed multistage under floor ram, wear resistant, weather resistant and rust resistant with safety valve

Underrun protection crossbar and approved towing preparation

Lights according to regulations

\* Available while stocks last

\* AWAITING EQUIPMENT TYPE APPROVAL



Overall dimensions with equipment L= 6280 mm

NOTE: The information and images - including the colors of the products - concerning equipment, external appearance, measurements, etc. are to be considered purely indicative and in no way binding.

TITAN reserves the right to change features, specifications, data, prices without notice. The prices indicated on the Site are in no way binding for contractual purposes and may vary according to the duration of the price list. Prices are always VAT free.

For updated and punctual information on products and prices, TITAN invites users to contact its sales network.